




DTH-RoX MU

Multi-use system for down the hole hammer

- Made for applications where the casing has to be removed from the ground.
- Designed to meet durability standards for removable equipment
- Double groove design* in the casing shoe
- Made using the best materials available
- Available for all the common down the hole hammers
- Ideal for piling, anchoring, and site investigation



DTH-RoX Multi-Use pilot bit



DTH-RoX Multi-Use ring bit

DTH-RoX MU Pilot bit

Item size	Casing				Pilot bit		Hammer	Weight	
	[mm]	[in]	[mm]	[in]	[mm]	[in]		[kg]	[lbs]
114.3-10	114,3	4 ½	10,0	0.394	92,5	3.642	3"	7	14
127-10	127,0	5	10,0	0.394	105,2	4.142	3 ½"	9	20
139.7-10	139,7	5 ½	10,0	0.394	117,5	4.626	4"	13	29
152.4-10	152,4	6	10,0	0.394	130,6	5.142	4"	17	37
168.3-10	168,3	6 ¾	10,0	0.394	146,0	5.748	5"	22	48
177.8-10	177,8	7	10,0	0.394	155,0	6.102	5"	28	61
193.7-10	193,7	7 ¾	10,0	0.394	172,0	6.772	6"	35	77
219.1-12.7	219,1	8 ¾	12,7	0.500	192,0	7.717	6"	40	88
273-12.7	273,0	10 ¾	12,7	0.500	243,0	9.567	8"	80	177
323.9-12.7	323,9	12 ¾	12,7	0.500	293,0	11.535	8"	120	265
355.6-12.7	355,6	14	12,7	0.500	326,0	12.835	8-12"	174	383
406.4-12.7	406,4	16	12,7	0.500	374,0	14.724	10-12"	236	520
508-15	508,0	20	15,0	0.591	472,0	18.583	12-15"	540	1191
609.6-12.7	609,6	24	12,7	0.500	581,0	22.874	18"	780	1720

DTH-RoX MU Ring bit

Item size	Casing				Ring bit				Weight	
	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[kg]	[lbs]
114.3-10	114,3	4 ½	10,0	0.394	78,0	3.071	122,0	4.803	6	12
127-10	127,0	5	10,0	0.394	95,0	3.740	136,0	5.354	7	14
139.7-10	139,7	5 ½	10,0	0.394	104,0	4.094	147,0	5.787	8	17
152.4-10	152,4	6	10,0	0.394	115,8	4.559	159,5	6.280	9	20
168.3-10	168,3	6 ¾	10,0	0.394	129,0	5.079	178,0	7.008	11	24
177.8-10	177,8	7	10,0	0.394	142,0	5.591	191,0	7.520	12	26
193.7-10	193,7	7 ¾	10,0	0.394	154,0	6.063	204,0	8.031	14	30
219.1-12.7	219,1	8 ¾	12,7	0.500	172,0	6.772	229,0	9.016	17	37
273-12.7	273,0	10 ¾	12,7	0.500	211,0	8.307	286,0	11.260	32	71
323.9-12.7	323,9	12 ¾	12,7	0.500	257,0	10.118	338,0	13.307	51	113
355.6-12.7	355,6	14	12,7	0.500	305,0	12.008	368,0	14.488	47	104
406.4-12.7	406,4	16	12,7	0.500	328,0	12.913	423,0	16.654	75	166
508-15	508,0	20	15,0	0.591	414,0	16.299	526,0	20.709	120	265
609.6-12.7	609,6	24	12,7	0.500	554,0	21.811	645,0	25.394	150	331